

FIG. 1





FIG. 2








FIG. 3








FIG. 7

H&E S/N	Side	Date Marked on Board	Test 1		Test 2		Test 3	
			Deflection @ 500 lbs.in		Deflection 1 Board @ 500 lbs.in		Max. Load, lbs/Deflection/Failure	
1	A	12-94	1.975		2.282		1527 lbs/6.385"/simple tension	
1	B	12-94	2.002		2.034			
2	A	12-94	2.378		2.308		1648 lbs/7.760"/full deflection reached with no failure	
2	B	12-94	2.508		2.271			
3	A	12-94	2.157		2.124		1652 lbs/6.844"/simple tension	
3	B	12-94	1.996		2.051			
4	A	11-94	2.002		2.174		1774 lbs/7.438"/full deflection reached with no failure	
4	B	11-94	2.005		2.112			
5	A	11-94	1.594		N/A		2147 lbs/6.785"/cross-grain tension failure	
5	B	11-94	1.810		N/A			
6	A	11-94	1.914		N/A		1008 lbs/4.275"/simple tension	
6	B	11-94	2.081		N/A			

FIG. 8

Comparison Results			
	Pinned	Solid	Laminated
Modulus of Elasticity	$2.0 \times 10^6$	$1.8 \times 10^6$	$2.15 \times 10^6$
Flexural Stress	2,600 psi	2,200 psi	2,900 psi
Horizontal Sheer Stress	120 psi	90 psi	145 psi

FIG. 9

Failure Results		
Type of board	Average Failure Load (lbs)	Comments
Pinned	2,700 psi	One member out of three fails first
Solid	2,200 psi	Whole Unit Fails
Laminated	2,400 psi	Whole Unit Fails

FIG. 10

Deflection Results		
Type of board (7 ft span)	Deflection @ 50 psf Load (in)	OSHA Allowable Deflection (in)
Pinned	0.73	1.4
Solid	0.81	1.4
Laminated	0.73	1.4

10035996.022802